

Description

Fastener Length: 5/8", Hole Diameter: 3/64", Thread: 6-32, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN500AD610
Minimum Qty (MOQ):	95 EA
NSN:	5305-00-061-5308
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN500AD6-10 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.563 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	0.625 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.208 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.089 Inches Minimum And 0.096 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	32
Screw Material:	Steel Comp 302 Or Steel Comp 303se Or Steel Comp 304 Or Steel Comp 316
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN500AD6-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.