

P/N AN500AD8-7

Description

Fastener Length: 13/32", Hole Diameter: 3/64", Thread: 8-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN500AD87
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-150-3084
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN500AD8-7 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.344 Inches Minimum And 0.437 Inches Maximum
Fastener Length:	0.406 Inches Minimum And 0.437 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.250 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.106 Inches Minimum And 0.113 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.164 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Comp 302 Or Steel Comp 303se Or Steel Comp 304 Or Steel Comp 316
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	1 Type And 5s Style

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN500AD8-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.