

Description

Fastener Length: 7/16", Thread: 2-56, Thread Length: 7/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN500D27
Minimum Qty (MOQ):	50
NSN:	5305-00-061-0976
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN500D2-7 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.402 Inches Minimum And 0.438 Inches Maximum
Fastener Length:	0.438 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.124 Inches Minimum And 0.140 Inches Maximum
Head Height:	0.055 Inches Minimum And 0.062 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Comp 302 Or Steel Comp 303se Or Steel Comp 304 Or Steel Comp 316
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN500D2-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.