

Description

Fastener Length: 5/16", Thread: 3-48, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN500D35
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-059-2504
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN500D3-5 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.270 Inches Minimum And 0.312 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.145 Inches Minimum And 0.161 Inches Maximum
Head Height:	0.064 Inches Minimum And 0.070 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.099 Inches
Thread Quantity Per Inch:	48
Screw Material:	Steel Comp 302 Or Steel Comp 303se Or Steel Comp 304 Or Steel Comp 316
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN500D3-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.