

Description

Fastener Length: 7/32", Hole Diameter: 3/64", Thread: 5-40, Thread Length: 11/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN500D54
Minimum Qty (MOQ):	35 EA
NSN:	5305-01-365-3862
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N AN500D5-4 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.169 Inches Minimum And 0.250 Inches Maximum
Fastener Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.081 Inches Minimum And 0.088 Inches Maximum
Head Height:	0.106 Inches Minimum And 0.120 Inches Maximum
Hole Diameter:	0.045 Inches Minimum And 0.050 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.125 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Comp 302 Or Steel Comp 304
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc
Specification/standard Data:	88044-an500 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN500D5-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.