

**Description**

Fastener Length: 23/32", Hole Diameter: 3/64", Thread: 8-32, Thread Length: 43/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN500D812
Minimum Qty (MOQ):	70 EA
NSN:	5305-01-204-0977
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N AN500D8-12 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.657 Inches Minimum And 0.750 Inches Maximum
<b>Fastener Length:</b>	0.719 Inches Minimum And 0.750 Inches Maximum
<b>Head Style:</b>	Fillister
<b>Head Diameter:</b>	0.250 Inches Minimum And 0.270 Inches Maximum
<b>Head Height:</b>	0.106 Inches Minimum And 0.113 Inches Maximum
<b>Hole Diameter:</b>	0.045 Inches Minimum And 0.050 Inches Maximum
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Hole Quantity:</b>	1
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Comp 302 Or Steel Comp 316 Or Steel Comp 303se Or Steel Comp 304
<b>Screw Material Document And Classification:</b>	66 Assn Std All Material Responses
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Head Hole Configuration Style:</b>	Round
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	1 Type And 5s Style

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN500D8-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.