

# P/N AN500D8-4

### **Description**

Fastener Length: 19/64", Thread: 8-32, Thread Length: 3/16", AN500 series screw

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN500D84

Minimum Qty (MOQ): 25

NSN: 5305-01-043-7320

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N AN500D8-4 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.173 Inches Minimum And 0.250 Inches Maximum
Fastener Length:	0.296 Inches Minimum And 0.328 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.250 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.106 Inches Minimum And 0.113 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Comp 303se Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	1 Type And 4s Style

# **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/AN500D8-4">https://military-fasteners.com/screws/machine+screws/AN500D8-4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/AN500D8-4">https://military-fasteners.com/screws/machine+screws/AN500D8-4</a> and selecting the quantity you