

Description

Fastener Length: 7/16", Thread: 10-32, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN501A107
Minimum Qty (MOQ):	25 EA
NSN:	5305-00-156-2716
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN501A10-7 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.407 Inches Minimum And 0.438 Inches Maximum
Fastener Length:	0.407 Inches Minimum And 0.438 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.292 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.123 Inches Minimum And 0.130 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 5s Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN501A10-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.