

Description

Fastener Length: 3/16", Thread: 0-80, Thread Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN501D03
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-194-8470
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN501D0-3 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.132 Inches Minimum And 0.188 Inches Maximum
Fastener Length:	0.157 Inches Minimum And 0.188 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.083 Inches Minimum And 0.096 Inches Maximum
Head Height:	0.029 Inches Minimum And 0.038 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.060 Inches
Thread Quantity Per Inch:	80
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Comp 301 Or Steel Comp 302 Or Steel Comp 302b Or Steel Comp 303 Or Steel Comp 303se Or Steel Comp 304 Or Steel Comp 304l Or Steel Comp 305 Or Steel Comp 308 Or Steel Comp 309 Or Steel Comp 309s Or Steel Comp 310 Or Steel Comp 310s Or Steel Comp 314 Or Steel Comp 316 Or Steel Comp 316l Or Steel Comp 317 Or Steel Comp 321 Or Steel Comp 347 Or Steel Comp 348 Or Steel Comp 384 Or Steel Comp 385
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 4s Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN501D0-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.