

## P/N AN502-10-24

### **Description**

Fastener Length: 1-1/2", Thread: 10-32, Thread Length: 1-7/16"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN5021024

Minimum Qty (MOQ): 10 EA

NSN: 5305-00-150-9204

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N AN502-10-24 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.438 Inches Minimum
Fastener Length:	1.500 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.292 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.045 Inches Minimum And 0.050 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 4037 Or Steel Comp 8630
Screw Material Document And Classification:	Ams 6300 Assn Std 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response
Thread Series Designator:	Unf

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/AN502-10-24">https://military-fasteners.com/screws/machine+screws/AN502-10-24</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/AN502-10-24">https://military-fasteners.com/screws/machine+screws/AN502-10-24</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/AN502-10-24">https://military-fasteners.com/screws/machine+screws/AN502-10-24</a> and selecting the quantity you want then click "add to cart".