

Description

Fastener Length: 1-1/8", Thread: 1/4-28, Thread Length: 1-3/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN50241618
Minimum Qty (MOQ):	30 EA
NSN:	5305-00-271-5234
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN502-416-18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.047 Inches Nominal
Fastener Length:	1.125 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.389 Inches Minimum And 0.414 Inches Maximum
Head Height:	0.161 Inches Minimum And 0.170 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Screw Material:	Steel Comp 4037 Or Steel Comp 8630
Screw Material Document And Classification:	An-s-9 Mil Std 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN502-416-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.