

P/N AN502-416-18

Description

Fastener Length: 1-1/8", Thread: 1/4-28, Thread Length: 1-3/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: AN50241618

Minimum Qty (MOQ): 10

NSN: 5305-00-271-5234

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN502-416-18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.047 Inches Nominal
Fastener Length:	1.125 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.389 Inches Minimum And 0.414 Inches Maximum
Head Height:	0.161 Inches Minimum And 0.170 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Screw Material:	Steel Comp 4037 Or Steel Comp 8630
Screw Material Document And Classification:	An-s-9 Mil Std 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN502-416-18 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.