



Military-Fasteners.com

P/N AN503-10-18

Description

length: 1-1/8", thread: 10-24, steel - cadmium plated - drilled head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN5031018
Minimum Qty (MOQ):	10
NSN:	5305-00-150-9219
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN503-10-18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.031 Inches Minimum And 1.062 Inches Maximum
Fastener Length:	1.063 Inches Minimum And 1.125 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.292 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.045 Inches Minimum And 0.050 Inches Maximum
Hole Diameter:	0.046 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 1 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN503-10-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.