

## P/N AN503-416-8

### **Description**

Fastener Length: 15/32", Hole Diameter: 1/16", Thread: 1/4-20, Thread Length: 13/32"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	AN5034168
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-150-9269
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N AN503-416-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.391 Inches Minimum And 0.454 Inches Maximum
Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.389 Inches Minimum And 0.414 Inches Maximum
Head Height:	0.161 Inches Minimum And 0.170 Inches Maximum
Hole Diameter:	0.062 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.250 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/AN503-416-8">https://military-fasteners.com/screws/machine+screws/AN503-416-8</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.