

Description

Fastener Length: 15/16", Thread: 10-24, Thread Length: 53/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN50510R15
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-023-6235
Schedule B:	7318.15.6080
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N AN505-10R15 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.708 Inches Minimum And 0.840 Inches Maximum
Fastener Length:	0.906 Inches Minimum And 0.937 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.348 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	82.0 Degrees Nominal
Screw Material:	Steel Comp 1010
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 2c Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN505-10R15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.