

Description

Fastener Length: 15/16", Thread: 10-24, Thread Length: 53/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | AN50510R15 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-01-023-6235 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N AN505-10R15 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.708 Inches Minimum And 0.840 Inches Maximum |
| Fastener Length: | 0.906 Inches Minimum And 0.937 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.348 Inches Minimum And 0.385 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 60000 Pounds Per Square Inch |
| Countersink Angle: | 82.0 Degrees Nominal |
| Screw Material: | Steel Comp 1010 |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 3 Type And 2c Style |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN505-10R15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.