

Description

Fastener Length: 1/2", Thread: 2-56, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN50528 |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5305-01-195-5804 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N AN505-2-8 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.433 Inches Minimum And 0.500 Inches Maximum |
| Fastener Length: | 0.469 Inches Minimum And 0.500 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.156 Inches Minimum And 0.172 Inches Maximum |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.086 Inches |
| Thread Quantity Per Inch: | 56 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Screw Material: | Steel Comp 1010 |
| Screw Material Document And Classification: | Qq-s-671 Fed Spec Single Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty1 Cl3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN505-2-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.