

Description

Fastener Length: 19/32", Thread: 1/4-20, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN50541610
Minimum Qty (MOQ):	25 EA
NSN:	5305-00-958-5245
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN505-416-10 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.341 Inches Minimum And 0.472 Inches Maximum
Fastener Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.452 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel
Screw Material Document And Classification:	66 Fed Std Single Material Response Or Astma108 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Or Mil-c-81562,ty 2,cl Mil Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 2c Style
Departure From Cited Designator:	As Modified By Material

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN505-416-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.