

# P/N AN505-6R44

### **Description**

Fastener Length: 2-21/32", Thread: 6-32, Thread Length: 1-3/4

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	AN5056R44
Minimum Qty (MOQ):	10
NSN:	5305-00-883-9304
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N AN505-6R44 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.750 Inches Minimum
Fastener Length:	2.656 Inches Minimum And 2.750 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.249 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel Comp 430 Or Steel Comp 302 Or Steel Comp 316 Or Steel Comp 303 Or Steel Comp 303se
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/AN505-6R44">https://military-fasteners.com/screws/machine+screws/AN505-6R44</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.