

P/N AN505B6-5

Description

Fastener Length: 9/32", Thread: 6-32, Thread Length: 13/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	AN505B65
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-151-1008

Schedule B: 8535.90.8040

ECCN: 9A991

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper



^{*} See page 2 for technical characteristics

P/N AN505B6-5 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.198 Inches Minimum And 0.229 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.249 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Copper Alloy
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	I Type And 2s Style

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN505B6-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/AN505B6-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/AN505B6-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/AN505B6-5 and selecting the quantity you want then click "add to cart".