

Description

Fastener Length: 3/16", Thread: 2-56, Thread Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN505C22
Minimum Qty (MOQ):	30 EA
NSN:	5305-00-282-2289
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN505C2-2 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.152 Inches Minimum And 0.188 Inches Maximum
Fastener Length:	0.156 Inches Minimum And 0.188 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.150 Inches Minimum And 0.172 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel Comp 303 Or Steel Comp 303se Or Steel Comp 430 Or Steel Comp 302
Screw Material Document And Classification:	Mil-s-7720 Mil Spec 1st Material Response Or Mil-s-18732 Mil Spec 2nd Material Response Or Qq-s-763 Fed Spec 3rd Material Response Or Mil-s-7720 Mil Spec 4th Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN505C2-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.