

Description

Fastener Length: 1/4", Thread: 2-56, Thread Length: 7/32

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN505C25
Minimum Qty (MOQ):	10
NSN:	5305-00-272-4374
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN505C2-5 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.230 Inches Minimum
Fastener Length:	0.312 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.150 Inches Minimum And 0.172 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel Comp 430 Or Steel Comp 303 Or Steel Comp 303se Or Steel Comp 316
Screw Material Document And Classification:	Qq-a-763 Cl Iv Fed Spec 1st Material Response Or Mil-s-7720 Comp Fm Mil Spec 2nd Material Response Or Mil-s-7720 Comp Fm Mil Spec 3rd Material Response Or Mil-s-7720 Comp G Mil Spec 4th Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN505C2-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.