

Description

Fastener Length: 3/16", Thread: 5-40, Thread Length: 3/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN505C53
Minimum Qty (MOQ):	100
NSN:	5305-00-271-3433
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN505C5-3 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.138 Inches Minimum And 0.188 Inches Maximum
Fastener Length:	0.156 Inches Minimum And 0.188 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.225 Inches Minimum And 0.252 Inches Maximum
Head Height:	0.043 Inches Minimum And 0.053 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.125 Inches
Thread Quantity Per Inch:	40
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel Comp 303 Or Steel Comp 303se Or Steel Comp 430 Or Steel Comp 302
Screw Material Document And Classification:	Mil-s-7720 Mil Spec 1st Material Response Or Mil-s-18732 Mil Spec 2nd Material Response Or Qq-s-763 Fed Spec 3rd Material Response Or Mil-s-7720 Mil Spec 4th Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN505C5-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.