

**Description**

Fastener Length: 1/4", Thread: 5-40, Thread Length: 3/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | AN505C54                                  |
| Minimum Qty (MOQ):      | 10 EA                                     |
| NSN:                    | 5305-00-588-9761                          |
| Schedule B:             | 7318.15.2091                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N AN505C5-4 Specifications

|                                                             |                                               |
|-------------------------------------------------------------|-----------------------------------------------|
| <b>Thread Class:</b>                                        | 2a                                            |
| <b>Thread Direction:</b>                                    | Right-hand                                    |
| <b>Thread Length:</b>                                       | 0.094 Inches Minimum And 0.188 Inches Maximum |
| <b>Fastener Length:</b>                                     | 0.219 Inches Minimum And 0.250 Inches Maximum |
| <b>Head Style:</b>                                          | Flat Countersunk                              |
| <b>Head Diameter:</b>                                       | 0.225 Inches Minimum And 0.252 Inches Maximum |
| <b>Internal Drive Style:</b>                                | Slot                                          |
| <b>Nominal Thread Diameter:</b>                             | 0.125 Inches                                  |
| <b>Thread Quantity Per Inch:</b>                            | 40                                            |
| <b>Minimum Tensile Strength:</b>                            | 80000 Pounds Per Square Inch                  |
| <b>Countersink Angle:</b>                                   | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| <b>Screw Material:</b>                                      | Steel Comp 303 Or Steel Comp 303se            |
| <b>Screw Material Document And Classification:</b>          | Astm A582 Assn Std All Material Responses     |
| <b>Screw Surface Treatment:</b>                             | Passivate                                     |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response    |
| <b>Thread Series Designator:</b>                            | Unc                                           |
| <b>Nondefinitive Spec/std Data:</b>                         | 1 Type And 2s Style                           |
| <b>Departure From Cited Designator:</b>                     | As Mod By Matl                                |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN505C5-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.