

Description

Fastener Length: 1/4", Thread: 5-40, Thread Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN505C54
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-588-9761
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN505C5-4 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.094 Inches Minimum And 0.188 Inches Maximum
Fastener Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.225 Inches Minimum And 0.252 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.125 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel Comp 303 Or Steel Comp 303se
Screw Material Document And Classification:	Astm A582 Assn Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	1 Type And 2s Style
Departure From Cited Designator:	As Mod By Matl

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN505C5-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.