

Description

Fastener Length: 9/16", Thread: 6-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN505C69 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-00-638-0836 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N AN505C6-9 Specifications

| | |
|--|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.500 Inches Minimum And 0.562 Inches Maximum |
| Fastener Length: | 0.562 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.249 Inches Minimum And 0.279 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Screw Material: | Steel Comp 303 Or Steel Comp 303se Or Steel Comp 430 Or Steel Comp 302 |
| Screw Material Document And Classification: | Mil-s-7720 Mil Spec 1st Material Response Or Mil-s-18732 Mil Spec 2nd Material Response Or Qq-s-763 Fed Spec 3rd Material Response Or Mil-s-7720 Mil Spec 4th Material Response |
| Screw Surface Treatment: | Passivate |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN505C6-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.