

Description

Fastener Length: 2-21/32", Thread: 6-32, Thread Length: 2-33/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN505C6R44
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-059-0170
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN505C6R44 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	2.511 Inches Minimum And 2.667 Inches Maximum
Fastener Length:	2.656 Inches Minimum And 2.750 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.249 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	82.0 Degrees Nominal
Screw Material:	Steel Comp 301 Or Steel Comp 302 Or Steel Comp 303 Or Steel Comp 303se Or Steel Comp 304 Or Steel Comp 304l Or Steel Comp 305 Or Steel Comp 308 Or Steel Comp 309 Or Steel Comp 310 Or Steel Comp 310s Or Steel Comp 314 Or Steel Comp 316 Or Steel Comp 316l Or Steel Comp 317 Or Steel Comp 321 Or Steel Comp 323 Or Steel Comp 324 Or Steel Comp 347 Or Steel Comp 348 Or Steel Comp 385
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 2c Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN505C6R44> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.