

Description

Fastener Length: 3/8", Thread: 6-32, Thread Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN505C6R6
Minimum Qty (MOQ):	50
NSN:	5305-00-208-0771
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN505C6R6 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.375 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.249 Inches Minimum And 0.279 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel Comp 303 Or Steel Comp 303se Or Steel Comp 430 Or Steel Comp 302
Screw Material Document And Classification:	Mil-s-7720 Mil Spec 1st Material Response Or Mil-s-18732 Mil Spec 2nd Material Response Or Qq-s-763 Fed Spec 3rd Material Response Or Mil-s-7720 Mil Spec 4th Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN505C6R6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.