

**Description**

Fastener Length: 1-13/16", Thread: 8-32, Thread Length: 1-51/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN505C8R30
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-838-5312
Schedule B:	7318.15.6080
ECCN:	9A991.
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N AN505C8R30 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.782 Inches Minimum
<b>Fastener Length:</b>	1.813 Inches Minimum And 1.875 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.300 Inches Minimum And 0.332 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	80.0 Degrees Minimum And 82.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp 430 Or Steel Comp 303 Or Steel Comp 303se
<b>Screw Material Document And Classification:</b>	Astm A582 Assn Std 1st Material Response Or Mil-s-7720 Mil Spec 2nd Material Response Or Mil-s-7720 Mil Spec 3rd Material Response
<b>Screw Surface Treatment:</b>	Passivate
<b>Thread Series Designator:</b>	Unc
<b>Departure From Cited Designator:</b>	As Mod By Drive Style

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN505C8R30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.