

Description

Fastener Length: 1-13/16", Thread: 8-32, Thread Length: 1-51/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN505C8R30
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-838-5312
Schedule B:	7318.15.6080
ECCN:	9A991.
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN505C8R30 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.782 Inches Minimum
Fastener Length:	1.813 Inches Minimum And 1.875 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.300 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel Comp 430 Or Steel Comp 303 Or Steel Comp 303se
Screw Material Document And Classification:	Astm A582 Assn Std 1st Material Response Or Mil-s-7720 Mil Spec 2nd Material Response Or Mil-s-7720 Mil Spec 3rd Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc
Departure From Cited Designator:	As Mod By Drive Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN505C8R30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.