



Military-Fasteners.com

P/N AN505C8R34

Description

Fastener Length: 2-1/32", Thread: 8-32, Thread Length: 1-3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN505C8R34
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-306-5480
Schedule B:	7318.15.6080
ECCN:	9A991.
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN505C8R34 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.750 Inches Minimum
Fastener Length:	2.031 Inches Minimum And 2.125 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.300 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	Qq-s-763,series 400 Fed Spec Single Material Response Or Mil-s-7720,comp Fm Or G Mil Spec Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	lii Type And 2c Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN505C8R34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.