

P/N AN507-1032R9

Description

length: 9/16", thread: 10-32, 100°, flat head - non-strucural - cadmium plated carbon steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN5071032R9

Minimum Qty (MOQ): 100

NSN: 5305-00-217-2446

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN507-1032R9 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.531 Inches Minimum And 0.562 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.359 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	960 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 1010
Screw Material Document And Classification:	Qq-s-671 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf
Specification/standard Data:	81348-ff-s-92 Government Specification And 88044-an507/canceled/ Government Standard
Departure From Cited Designator:	As Modified By Material And Surface Treatment

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN507-1032R9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/AN507-1032R9 and selecting the quantity you