

Description

Fastener Length: 1-1/4", Thread: 1/4-28, Thread Length: 1-11/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN507428R20 |
| Minimum Qty (MOQ): | 95 EA |
| NSN: | 5305-00-156-2403 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N AN507-428R20 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.179 Inches Minimum |
| Fastener Length: | 1.188 Inches Minimum And 1.250 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.462 Inches Minimum And 0.507 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| End Item Identification: | W/s: Aircraft, Orion P-3 |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Steel Comp 2330 |
| Screw Material Document And Classification: | Sae Assn Std Single Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unf |
| Nondefinitive Spec/std Data: | 3 Type And 3c Style |
| Departure From Cited Designator: | As Modified By Material,as Modified By Min Tensile Strength,as Modified By Hardness Rating |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN507-428R20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.