

P/N AN507-832R9

Description

Fastener Length: 9/16", Thread: 8-32, Thread Length: 1/2

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: AN507832R9

Minimum Qty (MOQ): 25

NSN: 5305-00-337-2842

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N AN507-832R9 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.500 Inches Minimum And 0.562 Inches Maximum
Fastener Length:	0.562 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.300 Inches Minimum And 0.332 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Or Steel Comp 1010
Screw Material Document And Classification:	Qq-s-630 Fed Spec 2nd Material Response Or Qq-s-631 Fed Spec 2nd Material Response Or Qq-s-634 Fed Spec 2nd Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN507-832R9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.