

**Description**

Fastener Length: 3/32", Thread: 0-80, Thread Length: 5/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN51002
Minimum Qty (MOQ):	20 EA
NSN:	5305-00-151-2262
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N AN510-0-2 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.068 Inches Minimum And 0.108 Inches Maximum
<b>Fastener Length:</b>	0.094 Inches Minimum And 0.125 Inches Maximum
<b>Head Style:</b>	Flat Countersunk Undercut
<b>Head Diameter:</b>	0.101 Inches Minimum And 0.119 Inches Maximum
<b>Head Height:</b>	0.017 Inches Minimum And 0.026 Inches Maximum
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.060 Inches
<b>Thread Quantity Per Inch:</b>	80
<b>Minimum Tensile Strength:</b>	55000 Pounds Per Square Inch
<b>Countersink Angle:</b>	80.0 Degrees Minimum And 82.0 Degrees Maximum
<b>Screw Material:</b>	Steel
<b>Screw Surface Treatment:</b>	Cadmium
<b>Thread Series Designator:</b>	Unf
<b>Nondefinitive Spec/std Data:</b>	I Type And 2s Style

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN510-0-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.