



Military-Fasteners.com

P/N AN510-0-2

Description

Fastener Length: 3/32", Thread: 0-80, Thread Length: 5/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN51002 |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5305-00-151-2262 |
| Schedule B: | 7318.15.2010 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N AN510-0-2 Specifications

| | |
|------------------------------|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.068 Inches Minimum And 0.108 Inches Maximum |
| Fastener Length: | 0.094 Inches Minimum And 0.125 Inches Maximum |
| Head Style: | Flat Countersunk Undercut |
| Head Diameter: | 0.101 Inches Minimum And 0.119 Inches Maximum |
| Head Height: | 0.017 Inches Minimum And 0.026 Inches Maximum |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.060 Inches |
| Thread Quantity Per Inch: | 80 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Screw Material: | Steel |
| Screw Surface Treatment: | Cadmium |
| Thread Series Designator: | Unf |
| Nondefinitive Spec/std Data: | I Type And 2s Style |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN510-0-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.