

Description

Fastener Length: 3/32", Thread: 0-80, Thread Length: 5/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN51002
Minimum Qty (MOQ):	20 EA
NSN:	5305-00-151-2262
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN510-0-2 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.068 Inches Minimum And 0.108 Inches Maximum
Fastener Length:	0.094 Inches Minimum And 0.125 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.101 Inches Minimum And 0.119 Inches Maximum
Head Height:	0.017 Inches Minimum And 0.026 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.060 Inches
Thread Quantity Per Inch:	80
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	I Type And 2s Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN510-0-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.