

P/N AN515-10-6

Description

Fastener Length: 3/8", Thread: 10-24, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN515106

Minimum Qty (MOQ): 115 EA

NSN: 5305-00-984-6208

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN515-10-6 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.292 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.375 Inches Nominal
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	Mrap-cougar
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Steel Comp 1010 Or Steel Comp 1011 Or Steel Comp 1013
Screw Surface Treatment:	Cadmium Or Zinc
Screw Surface Treatment Document And	Sae/ams Qq-p-416, Ty2cl3 Assn Std Single Treatment Response Or Astm-b633 Assn Std Single Treatment
Classification:	Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	1 Type

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN515-10-6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.