P/N AN515-3R6

Description

Fastener Length: 3/8", Thread: 3-48, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN5153R6
Minimum Qty (MOQ):	80 EA
NSN:	5305-00-151-3164
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN515-3R6 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.302 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.344 Inches Minimum And 0.375 Inches Maximum
Head Style:	Round
Head Diameter:	0.169 Inches Minimum And 0.187 Inches Maximum
Head Height:	0.078 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.099 Inches
Thread Quantity Per Inch:	48
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel
Screw Material Document And Classification:	Astm A108 Assn Std Single Material Response Or 66 Fed Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 1c Style

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN515-3R6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.