

## **P/N AN515-4-5**

### **Description**

Fastener Length: 5/16", Thread: 4-40, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	AN51545
Minimum Qty (MOQ):	55 EA
NSN:	5305-00-206-0541
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N AN515-4-5 Specifications**

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.262 Inches Minimum And 0.312 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Round
Head Diameter:	0.193 Inches Minimum And 0.211 Inches Maximum
Head Height:	0.086 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Steel Or Steel Comp 1010
Screw Material Document And Classification:	Qq-s-630 Fed Spec 2nd Material Response Or Qq-s-631 Fed Spec 2nd Material Response Or Qq-s-634 Fed Spec 2nd Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/AN515-4-5">https://military-fasteners.com/screws/machine+screws/AN515-4-5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.