

**Description**

Fastener Length: 17/32", Thread: 4-40, Thread Length: 15/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN5154R8
Minimum Qty (MOQ):	75 EA
NSN:	5305-00-339-8802
Schedule B:	7318.15.6080
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N AN515-4R8 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.419 Inches Minimum And 0.469 Inches Maximum
<b>Fastener Length:</b>	0.500 Inches Minimum And 0.531 Inches Maximum
<b>Head Style:</b>	Round
<b>Head Diameter:</b>	0.193 Inches Minimum And 0.211 Inches Maximum
<b>Head Height:</b>	0.086 Inches Nominal
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	55000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Comp 1010
<b>Screw Material Document And Classification:</b>	Qq-s-671,ty Fs Or Equivalent Fed Spec Single Material Response
<b>Screw Surface Treatment:</b>	Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc
<b>Departure From Cited Document:</b>	As Mod By Rev 5

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN515-4R8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.