

P/N AN515-6R10

Description

Fastener Length: 19/32", Thread: 6-32, Thread Length: 19/32

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: AN5156R10

Minimum Qty (MOQ): 100

NSN: 5305-00-421-3514

Schedule B: 7318.15.6080

ECCN: EAR99









^{*} See page 2 for technical characteristics

P/N AN515-6R10 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Head Style:	Round
Head Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Height:	0.103 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Steel
Screw Material Document And Classification:	Qq-s-672 Comp Fs1010 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 1 Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN515-6R10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.