

Description

Fastener Length: 7/32", Thread: 6-32, Thread Length: 7/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN5156R4 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-151-1227 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N AN515-6R4 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Length: | 0.219 Inches Minimum And 0.250 Inches Maximum |
| Fastener Length: | 0.219 Inches Minimum And 0.250 Inches Maximum |
| Head Style: | Round |
| Head Diameter: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Head Height: | 0.103 Inches Nominal |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Screw Material: | Steel Comp 1010 |
| Screw Material Document And Classification: | Qq-s-671 Fed Spec Single Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN515-6R4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.