

Description

Fastener Length: 9/32", Thread: 6-32, Thread Length: 9/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN5156R5
Minimum Qty (MOQ):	80 EA
NSN:	5305-00-151-1228
Schedule B:	7318.15.6080
ECCN:	9A991.
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN515-6R5 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Round
Head Diameter:	0.240 Inches Minimum And 0.260 Inches Maximum
Head Height:	0.103 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Steel Comp 1010
Screw Material Document And Classification:	Qq-s-671 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,c1 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 1c Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN515-6R5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.