

Description

Fastener Length: 1-1/4", Thread: 8-32, Thread Length: 1-1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN515820
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-984-6198
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN515-8-20 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.250 Inches Minimum
Fastener Length:	1.250 Inches Nominal
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
iii End Item Identification:	Mrap - Cougar Tow; Mrap - Cougar Sabr/tow
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Screw Material:	Steel
Screw Material Document And Classification:	Astm A576 Assn Std Single Material Response Or Astm A108 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN515-8-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.