

Description

Fastener Length: 19/32", Thread: 8-32, Thread Length: 19/32

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN5158R10
Minimum Qty (MOQ):	50
NSN:	5305-00-207-1549
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN515-8R10 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Head Style:	Round
Head Diameter:	0.287 Inches Minimum And 0.309 Inches Maximum
Head Height:	0.120 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Steel Comp 1010
Screw Material Document And Classification:	Qq-s-633 Fed Spec Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN515-8R10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.