

P/N AN515-8R30

Military-Fasteners.com

Description

Fastener Length: 1-13/16", Thread: 8-32, Thread Length: 1-13/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	AN5158R30
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-281-9513
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN515-8R30 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.812 Inches Minimum And 1.875 Inches Maximum
Fastener Length:	1.812 Inches Minimum And 1.875 Inches Maximum
Head Style:	Round
Head Diameter:	0.287 Inches Minimum And 0.309 Inches Maximum
Head Height:	0.120 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Screw Material:	Steel Or Steel Comp 1010
Screw Material Document And Classification:	Astm A575 Assn Std Single Material Response Or Astm A576 Assn Std Single Material Response Or Astm A108 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/AN515-8R30</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.