



★ FASTENERS

Military-Fasteners.com

P/N AN515-8R6

Description

Fastener Length: 3/8", Thread: 8-32, Thread Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS35206-243](#)

| | |
|-------------------------|---|
| SKU / Model: | AN5158R6 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-00-206-0535 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N AN515-8R6 Specifications

| | |
|---|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.375 Inches Minimum |
| Fastener Length: | 0.375 Inches Nominal |
| Head Style: | Round |
| Head Diameter: | 0.287 Inches Minimum And 0.309 Inches Maximum |
| Head Height: | 0.107 Inches Minimum And 0.120 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 60000 Pounds Per Square Inch |
| Screw Material: | Steel |
| Screw Material Document And Classification: | Qq-s-634 Fed Spec Single Material Response Or Qq-s-637 Fed Spec Single Material Response Or 66 Fed Std Single Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 1 Type And 1 Design |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN515-8R6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.