

P/N AN515B6-8

Description

Fastener Length: 1/2", Thread: 6-32, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	AN212B08	
Minimum Qty (MOQ):	5 EA	
NSN:	5305-00-206-1288	
Schedule B:	7415.33.8050	

ECCN: 9A991

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper



^{*} See page 2 for technical characteristics

P/N AN515B6-8 Specifications

Thread Class:	2a	
Thread Direction:	Right-hand	
Thread Length:	0.438 Inches Minimum And 0.500 Inches Maximum	
Fastener Length:	0.500 Inches Nominal	
Head Style:	Pan	
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum	
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum	
Internal Drive Style:	Cross Recess Type 1	
Nominal Thread Diameter:	0.138 Inches	
Thread Quantity Per Inch:	32	
Minimum Tensile Strength:	57000 Pounds Per Square Inch	
Screw Material:	Copper Alloy	
Screw Material Document And Classification:	Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response	
Thread Series Designator:	Unc	

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/AN515B6-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/AN515B6-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/AN515B6-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/AN515B6-8 and selecting the quantity you want then click "add to cart".