

Description

Fastener Length: 19/32", Thread: 8-32, Thread Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | AN515B8R10 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-00-151-2863 |
| Schedule B: | 7415.33.8050 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N AN515B8R10 Specifications

| | |
|--|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.594 Inches Minimum And 0.625 Inches Maximum |
| Fastener Length: | 0.594 Inches Minimum And 0.625 Inches Maximum |
| Head Style: | Round |
| Head Diameter: | 0.287 Inches Minimum And 0.309 Inches Maximum |
| Head Height: | 0.120 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 55000 Pounds Per Square Inch |
| Screw Material: | Copper Alloy |
| Screw Material Document And Classification: | Qq-b-613 Fed Spec Single Material Response Or Qq-b-626 Fed Spec Single Material Response Or Qq-w-321 Fed Spec Single Material Response |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 3 Type And 1c Style |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN515B8R10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.